

## Elektroscherenbühnen

Typ	Arbeitshöhe in m			Hub- kraft in kg	Plattform- ausschub in m	Gewicht in kg	Einsatz- bereich: I=Innen, A=Aussen	abriebsarme Reifen	Pendel- achse	Differenzial- sperre	Allrad
	(= Plattformhöhe + 2 m)	Länge x Breite in m	Höhe mit/ ohne Geländer in m								
PB S06-7EC	5,8	1,31 x 0,76	1,95/1,59	240	0,55	615	I/A	x			
GS 1530	6,57	1,83 x 0,76	2,08	272	0,86	1257	I	x			
GS 1932	7,6	1,83 x 0,82	2,12/1,75	227	0,91	1516	I/A	x			
GS 1930	7,82	1,85 x 0,76	1,99/1,38	227	0,97	1306	I	x			
GS 2032	8,11	2,42 x 0,81	1,99/1,55	365	1	1550	I/A	x			
Compact 8	8,18	2,47 x 0,81	1,99/1,14	350	0,92	1730	I/A	x			
Y-64 EL 14	8,4	3,00 x 1,40	2,30/1,47	300	0,9	2390	I/A	x		x	
GS 2632	9,92	2,44 x 0,82	2,28/1,92	227	0,93	1984	I	x			
GS 2669 DC	9,7	3,76 x 1,75	2,59/1,88	680	1,52	4199	I/A	x	x		
GS 2646	9,8	2,41 x 1,17	2,26/1,68	454	0,91	2447	I/A	x			
						2.160 -					
Compact 10 N	10	2,48 x 0,81	2,18/1,40 – 1,77	230	0,92	2.190	I	x			
Compact 10	10,14	2,48 x 1,20	2,25/1,40	450	0,9	2330	I/A	x			
Y-83 EL 16	10,3	2,95 x 1,60	2,50/1,70	400	0,99	3000	I/A	x		x	
GS 3232	11,5	2,44 x 0,81	2,39/2,03	227	0,91	2352	I	x			
GS 3246	11,5	2,41 x 1,17	2,39/1,80	318	0,91	2812	I/A	x			
Compact 12	12	2,47 x 1,20	2,38/1,52	300	0,9	2630	I/A	x			
X 105 EL 16	12,5	1,83 x 3,40	2,80/2,02	350	1,48	4820	I/A	x		x	
X 105 EL 18	12,5	1,83 x 3,40	2,80/1,85	500	1,48	4940	I/A	x			
GS 4047	13,7	2,44 x 1,19	2,54/1,88	350	0,91	3221	I	x			
SL 125 18 E	14,5	4,23 x 1,82	3,05/2,35	1000	2,16	7380	I/A	x			
SL 130 E 20	15	3,50 x 2,05	2,97/2,17	500	2,08	6550	I/A	x			
S 151 19 E	15,3	4,20 x 1,93	3,30/2,36	500	2,25	9040	I/A	x			

## Elektroscherenbühnen

Typ	Arbeitshöhe in m (= Plattformhöhe + 2 m)		Länge x Breite in m	Höhe mit/ ohne Geländer in m	Hub- kraft in kg	Plattform- ausschub in m	Gewicht in kg	Einsatz- bereich: I=Innen, A=Aussen	abriebsarme Reifen	Pendel- achse	Differenzial- sperre	Allrad
<b>S 171 E 16</b>	17,03		2,21/2,34 x 3,18/3,20	3,03 - 3,18/ 2,21 - 2,34	400	1,00/2,25	5120	I/A	x			
<b>HL 151 EV</b>	17,1		4,43 x 2,35	3,16/2,39	500	1,75	5700	I/A	x			
<b>S 175-19 E 4x4</b>	17,8		4,20 x 1,93	2,54/3,45	500	2,25	9030	I/A	x	x	x	x
<b>B 165 EL 25</b>	18,5		4,70 x 2,50	3,34/2,56	650	1,87	9980	I/A	x		x	
<b>N 165 EL 12</b>	18,5		3,75 x 1,20	3,40/2,78	500	1,57	7985	I	x		x	
<b>SL 172 E 18</b>	19,2		4,78 x 1,80	3,48/2,70	750	1,85	9780	I/A	x			
<b>SL 180 E 12</b>	20		4,16 x 1,21	3,50/2,77	500	1,56	7800	I	x			
<b>N 195 EL 12</b>	21,4		3,70 x 1,20	3,77/3,02	500	1,55	9120	I	x		x	
<b>N 265 EL 13</b>	28,5		5,80 x 1,32	4,11/3,20	750	2,27	19370	I/A	x		x	